

M.T.O. Temporary Wildlife Fence

Our wildlife fence is used as temporary barrier devices in locations where it is necessary to redirect animal movement, whether for containment, exclusion or protection. When installed correctly, wildlife fence is an effective barrier device but failure can occur if the product is installed incorrectly or is not properly maintained.

Note: Meets M.T.O. Specification O.P.S.D dated December, 2017.

FABRIC DATA			
Property	Test Method	MARV Imperial	Marv Metric
Tensile Strength (Grab)	ASTM D-4632	125 x 124 LBS	556 x 551.6 N
Elongation	ASTM D-4632	15% x 15%	15% x 15%
CBR Puncture	ASTM D-6241	325 LBS	1,445.7 N
Trapezoidal Tear	ASTM D-4533	65 X 65 LBS	289.1 x 289.1 N
UV Resistance (500hrs)	ASTM D-4355	70%	0.7
Apparent Opening Size (AOS) *	ASTM D-4751	30 US STD. SIEVE	.60mm
Permittivity	ASTM D-4491	0.1 SEC -1	0.1 SEC -1
Water Flow Rate	ASTM D-4491	8 GPM/FT ²	326 lpm/m ²
Roll Size		4'x 100'	1.22m x 30.5m
PICKET DATA			
Hardwood Pickets/roll		13	13
Hardwood Picket Size		1.5" x 1.5" x 60"	3.81cm x 3.81cm x 1.52m